


AIP IRELAND
STANDARD DEPARTURE CHART
INSTRUMENT (SID) ICAO

TRANS ALT 5000FT
TRANS LEVEL by ATC

Kerry TWR	123.325
Kerry GND	121.600
Shannon Control	124.700
ATIS	118.025

KERRY RWY 26
CAT A,B
SHA 3A, CRK 3A, KER 3A



CHANGE: Caution Note 3 added

SHA 3A CAT A/B SID RWY26

SHA3A

Navigation Performance	Path Terminator	WPT Name	Latitude (N), Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track/ Magnetic Track	Upper limit/ Lower Limit	Speed Limit (kts)	Remarks
RNAV1	CF	RWY26	-	-	-	252.2/ 257	-	-	-
RNAV1	CF	KY001	520932.2/ 0093829.8	Fly-Over	4.0	252.2/ 257	-4000/ +1400	-	-
RNAV1	CF	KY002	521219.1/ 0093928.2	Fly-By	1.0	042.1/ 047	-4000/ +2800	-	R
RNAV1	TF	SHA	524315.6/ 0085306.8	Fly-By	42.0	042.2/ 047	4000	-	-

CRK 3A CAT A/B SID RWY26

CRK3A

Navigation Performance	Path Terminator	WPT Name	Latitude (N), Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track/ Magnetic Track	Upper limit/ Lower Limit	Speed Limit (kts)	Remarks
RNAV1	CF	RWY26	-	-	-	252.2/ 257	-	-	-
RNAV1	CF	KY001	520932.2/ 0093829.8	Fly-Over	4.0	252.2/ 257	-4500/ +1400	-	-
RNAV1	CF	KY003	520611.5/ 0093420.3	Fly-By	2.8	111.0/ 115	-4500/ +3300	-	L
RNAV1	TF	CRK	515026.2/ 0082939.4	Fly-By	43.0	111.1/ 115	4500	-	-

KER 3A CAT A/B SID RWY26

KER3A

Navigation Performance	Path Terminator	WPT Name	Latitude (N), Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track/ Magnetic Track	Upper limit/ Lower Limit	Speed Limit (kts)	Remarks
RNAV1	CF	RWY26	-	-	-	252.2/ 257	-	-	-
RNAV1	CF	KY001	520932.2/ 0093829.8	Fly-Over	4.0	252.2/ 257	-4000/ +1400	-	-
RNAV1	CF	KER	521055.8/ 0093128.2	Fly-By	4.5	041.6/ 046	4000	-	L